

HLX 125

4 GEAR

TECHNICAL SPECIFICATIONS

ENGINE & TRANSMISSION

Type	4 Stroke, Natural Air Cooled
Starting	Electric Start & Kick Start
Engine Displacement (cc)	124.53
Clutch & Transmission	Wet, Multi-Plate Type
Maximum Power in kW	8.09 @ 8000 RPM
Maximum Torque in Nm	10.8 @ 5500 RPM
No. of Gears	4 Speed
Pattern	1-N-2-3-4

CHASSIS DIMENSIONS & WEIGHT

Overall Length(mm)	2000
Overall Height(mm)	1030
Overall Width(mm)	745
Wheel Base(mm)	1260
Ground Clearance(mm)	180(unladen)
Kerb Weight(kg)	115

SUSPENSION

Front Type	Telescopic Oil Damped
Rear Type	5-Step Adjustable Hydraulic Shocks

TYRES

Front Tyre	2.75x17, 41P, Duragrip
Rear Tyre	100/90x17, 51P, Duragrip

BRAKES

Front Drum(mm)	130mm Drum
Rear Drum(mm)	130mm Drum

ELECTRICALS

Battery Type & Spec	MF Battery, 12V 5Ah
---------------------	---------------------

CAPACITIES

Fuel Tank(Litre)	12
------------------	----



Call-Free:

080 00 11 22 33



**GO FURTHER FOR LESS AND
INCREASE YOUR EARNINGS!**

HLX 125 **4 GEAR**



LAST MILE WORKHORSE!



LARGER SEAT FOR EXTRA SPACE
AND MAXIMUM COMFORT.



DURABLE ENGINE THAT GIVES MORE
POWER & IMPROVED ECONOMY.



DURABLE AND STYLISH
RUST-FREE ALLOY WHEELS.